Basket Trolley KTW-1-5



Basket transport trolley in low version for empty and loaded 19.7 \times 19.7" (500 \times 500 mm) crockery baskets. Trolley made entirely of high-quality stainless steel, robust, self-supporting and hygienic design. Tubular frame rack made of square tubes with plastic end caps and welded L-shaped shelf rails for holding 19.7 \times 19.7" (500 \times 500) to 20.3 \times 20.3" (515 \times 515 mm) baskets at distances of 5.9" (150 mm). Push-through protections on both sides as per DIN EN 18867-2. Cover plate folded on all sides, rebated inwards, with sound insulation on the underside, as worktop or storage space for additional basket. Gallery on three sides made of round tubes, permanently fixed to the side pillars, also usable as push bar thanks to ergonomic design. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ϕ 4.9" (125 mm), with pin fastening.

The Hupfer basket transport trolley KTW-1-5 has outstanding handling properties due to its very low empty weight in comparison to other products and a gallery that can be used as a push bar, as well as the greatest usable height of 145 mm between the shelf rails.



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Maximum dimension:	500x500 to 515x515 mm insert
	dimension
Capacity:	5 crockery baskets
Modular dimension:	150 mm
Rectangular tube frame:	25 × 25 mm
Worktop height:	990 mm
Worktop material thickness:	1.0 mm
Round tube gallery:	ø 20 mm
Payload:	80 kg/176 lbs
Castors:	4 swivel castors, 2 with lock, 125 ø
Main construction:	Open
Design:	Low
Weight:	17.63 kg
Width:	630 mm
Depth:	638 mm
Height:	1061 mm

All information / dimensions are approximate, technical changes reserved. © Hupfer



() www.comcater.com.au () contactus@comcater.com.au