



NON HEATED UNIVERSAL CROCKERY DISPENSER WITH SLOTTED PANELLING FOR COOLING

Mobile universal crockery dispenser for storing round and rectangular crockery items with a diameter or edge lengths of 80 to 280mm. The dispenser in self-supporting and hygienic design is made of high-quality stainless steel. Features closed, smooth outer housing with a stacking compartment including compartment inner panelling and removable stacking platform made of plastic-coated stainless steel grating with a ball bearing platform guide.

Offers a consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above. Optimum manoeuvrability thanks to bow-shaped handle on upper side of structure. Two massive polymer corner bumpers serve as bumpers in the direction of transport to protect the equipment as well as building-side walls from being damaged. Dispenser runs on 4 x 125mm diameter swivel casters, 2 of which have wheel locking brakes, fastened by means of screw-on plates and several screws.

The Hupfer universal crockery dispenser UST-57-28 provides a wide range of variation options for stacking tableware with different shapes and dimensions, and features the smallest external dimensions and the lowest empty weight in comparison to other products, while the plug-in bow-shaped handle ensures optimal handling properties, especially when used in niches of serving counters. The push handle also guarantees effective protection against injuries to the operators hands. The installation height of 900 mm is the standard working height in food distribution.



DIMENSIONS

510D x 750W x 900H mm

TECHNICAL DATA

Maximum Platform Basket Dimension: 570 x 280mm

Capacity: Up to 510 parts w/o cover, 615 with cover, 565mm max stacking height without cover

Stainless steel guide bars: 2, 16 centering slots

Castors: 4 swivel castors 125mm diameter, 2 with locks

Main construction: Closed, single walled with slotted side panelling to assist cooling

Net Weight of the Appliance: 42 kg

Load Capacity: 100 kg

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.





