



Specifically designed for high - volume frying Frymaster's electric fryers are enhanced for improved efficiency, convenience and serviceability. The RE114 (14kw) and RE117 (17kw) electric fryers have 25 litres oil capacity. The frying area is 356mm x 394mm. The temperaters ensor, mounted on the elements, permits instant response to loads. Easy to clean rotating electric elements have low watt density for increased reliability and extended life.

A large cold zone catches crumbs and sediment from the frying area. Open pot design stainless steel frypot and coldzone can becleaned and wiped down by hand.

Split pot models (RE114-2SD, RE117-2CSD) have 2 x12.5L pots and individual thermostats.

STANDARD FEATURES

- Heating elements lift and hold upright for easy cleaning
 Ribbon type, low watt density, long life heating
- elements
 Cold zone. 1-1/4" (32 mm) IPS balltype drain valve
- Open frypot design easy to clean
 Boil-out mode for easy cleaning
- Stainless steel frypot
- Cover(s)
 Electronic Timer Controller


OPTIONAL FEATURES


- Castors 8101494 (Non Brake), 8102970 (Brake)
- In-Built Filtration System 2 to 4 fryers can be batteried to right side of filter
- (refer FPRE Series Spec Sheet)

 Automatic basket lifts BLC
- Fish Plate S51058
- Capping Strip 8235810 CM3.5 Computer Controller



shown with optional castors





DIMENSIONS

External: 397W x 786D x 1152H mm

Clearance: Sides and rear 152mm, Front 610mm

Net Weight: 68kg

TECHNICAL DATA

Power Supply: 415V, 3 Phase, 20/24 A. (Supplied with 2m lead only)

Total Output: RE114(C): 14kw RE114-2(C): 14kw RE117(C): 17kw RE117-2(C): 14kw

Drain Height: 299mm

PRODUCTION CHIPS FROM FROZEN

RE114(C): 31kg per hour RE117(C): 32kg per hour

CONTROLLER AS STANDARD


Electronic Timer Controller or (C) = CM3.5 Computer

SHIPPING DATA

Shipping Weight: 86kg

Shipping Dimensions: 550W x 950D x 1470H mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



TOP VIEW



