

The Extra Heavy Duty Master Series' modular approach combines the convenience of custom kitchen design with proven, premium quality components to deliver world class functionality.

Featuring stainless steel construction front and sides, large front 'plate rail' 191mm deep and 2.5mm thick.

2 piece burners are easy to remove and clean with protected individual pilot lights and flame failure as standard. Large 683mm deep work surface fits two 300mm pots easily and grate design allows pots to slide across the surface easily. Premium 25mm thick griddle with powerful cast iron 'H' burners controlled by Hi-Lo valve for even heat distribution.

Large easy-to-use control knobs sit atop the fully porcelain interior standard oven that accepts full sized sheet pans in both directions with 4-position rack guides. A 42.2MJ 'H' oven burner with flame failure and a strong adjustable door.

STANDARD FEATURES

- 152mm chrome steel adjustable legs
- Stainless steel drip tray under open burners
- Piezo Spark ignition for oven
- Modular 1½" front manifold
- Removable front-mounted s/steel grease receptacle
- Removable ring grates over burners
- 250mm stainless steel backguard
- Electric Spark ignition on all pilots

OPTIONAL FEATURES

- Stainless steel oven interior, side(s) or main back
- Fully grooved griddle (or grooved sections)
- Additional oven rack
- Gas regulator ¾" or 1¼"
- Rear gas connection, ¾", 1", or 1¼"
- 4 swivel casters with front brakes
- End caps and cover (NC, Specify)
- Dais base (not for use with "RC" oven)
- Convection oven base, add C to model, eg MST42RC
- Stainless steel common front rail up to 1728mm wide (2 or more units in a battery)
- Gas flex hose & quick disconnect (¾", 1" or 1¼" x 5') w/restraining device

DIMENSIONS

External Dimension: 864W x 962D x 1174H mm
 Working height : 924mm
 Oven Interior : 667W x 737D x 343H mm
 Combustible wall clearance: Side: 356mm, Rear: 152mm

TECHNICAL DATA

Gas Type: Natural or LP

| | | |
|---------------|----------|----------|
| Total Output: | Natural | LP |
| | 147.65MJ | 142.35MJ |

| | | |
|-----------------|---------|---------|
| Burner Ratings: | Natural | LP |
| Open Burner | 36.9MJ | 36.9MJ |
| Griddle Burner | 31.65MJ | 31.65MJ |
| Oven Burner | 42.2MJ | 36.9MJ |

Gas Connection: 1½"

Shipping weight: MST42RE 202kg, MST42SE 157kg

AGA approval number

SC380

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

