GARLAND

MST44R & MST44S

864mm WIDE MASTER SERIES 4 BURNER RANGE & 4 BURNER WITH STORAGE BASE

The Extra Heavy Duty Master Series' modular approach combines the convenience of custom kitchen design with proven, premium quality components to deliver world class functionality.

Featuring stainless steel construction front and sides, large front 'plate rail' 191mm deep and 2.5mm thick.

2 piece burners are easy to remove and clean with protected individual pilot lights and flame failure as standard. Large 683mm deep work surface fits 400mm pots easily and grate design allows pots to slide across the surface easily.

Large easy-to-use control knobs sit atop the fully porcelain interior standard oven that accepts full sized sheet pans in both directions with 4-position rack guides. A 42.2MJ 'H' oven burner with flame failure and a strong adjustable door.

STANDARD FEATURES

- 152mm chrome steel adjustable legs
- Stainless steel drip tray under open burners
- Piezo Spark ignition for oven
- Modular 1¼" front manifold
- 250mm stainless steel backguard
- Removable ring grates over burners

OPTIONAL FEATURES

- Stainless steel oven interior, side(s) or main back
- Fully grooved griddle (or grooved sections)
- Additional oven rack
- Gas regulator ¾" or 1¼"
- Rear gas connection, ¾", 1", or 1¼"
- 4 swivel casters with front brakes
- End caps and cover (NC, Specify)
- Dais base (not for use with "RC" oven)
- Convection oven base, add C to model, eg MST44RC
- Stainless steel common front rail up to 1728mm wide
- (2 or more units in a battery)
- Gas flex hose & quick disconnect (%", 1" or 1¼" x 5') w/restraining device
- Electric Spark ignition on all pilots Suffix -E models

DIMENSIONS

External Dimension: 864W x 962D x 1174H mm

Working height: 924mm

Oven Interior : 667W x 737D x 343H mm

Combustible wall clearance: Side: 356mm, Rear: 152mm

TECHNICAL DATA

Gas Type: Natural or LP		
Total Output:	Natural 189.8MJ	LP 184.5MJ
Burner Ratings: Open Burner Oven Burner	Natural 36.9MJ 42.2MJ	LP 36.9MJ 36.9MJ
Gas Connection: 1¼"		


Shipping weight: MST44R 200kg, MST44S 155kg

AGA approval number

SC380

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.





152mm

362mm

(∰)


864mm



contactus@comcater.com.au

864mm

LAdd 25mm for optional RC Motor



 (\boxtimes)



www.comcater.com.au