GARLAND

MST45RE & MST45SE

864mm WIDE MASTER SERIES DUAL TARGET TOP **RANGE & DUAL TARGET TOP WITH STORAGE BASE**

The Extra Heavy Duty Master Series' modular approach combines the convenience of custom kitchen design with proven, premium quality components to deliver world class functionality.

Featuring stainless steel construction front and sides, large front 'plate rail' 191mm deep and 2.5mm thick.

Dual cast-iron 'knuckle' burners sit below removable cast-iron ring and lid for concentrated heat at the target area with heat graduating further away from the target. Protected individual pilot lights and flame failure as standard. Large 683mm deep work surface fits six 300mm pots easily and the design allows pots to slide across the surface easily.

Large easy-to-use control knobs sit atop the fully porcelain interior standard oven that accepts full sized sheet pans in both directions with 4-position rack guides. A 42.2MJ 'H' oven burner with flame failure and a strong adjustable door.

STANDARD FEATURES

- 152mm chrome steel adjustable legs
- Piezo Spark ignition for oven
- 250mm stainless steel backguard
- Modular 1¼" front manifold

OPTIONAL FEATURES

- Stainless steel oven interior, side(s) or main back
- Fully grooved griddle (or grooved sections)
- Additional oven rack
- Gas regulator ¾" or 1¼"
- 4 swivel casters with front brakes
- End caps and cover (NC, Specify)
- Dais base (not for use with "RC" oven)
- Convection oven base, add C to model, eg MST45RC
- Stainless steel common front rail up to 1728mm wide
- (2 or more units in a battery)
- Gas flex hose & quick disconnect (¾", 1" or 1¼" x 5') w/restraining device
- Electric Spark ignition on all pilots Suffix -E models

DIMENSIONS

External Dimension: 864W x 962D x 1174H mm

Working height: 924mm

Oven Interior : 667W x 737D x 343H mm

Combustible wall clearance: Side: 356mm, Rear: 152mm

TECHNICAL DATA

Gas Type: Natural or LP		
Total Output:	Natural 126.6MJ	lp 121.3MJ
Burner Ratings: Target Burners Oven Burner	Natural 42.2MJ 42.2MJ	LP 42.2MJ 36.9MJ

Gas Connection: 1¼"


Shipping weight: MST45RE 232kg, MST45SE 186kg


AGA approval number


SC381

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.











1174mr



¹¹Add 25mm for optional RC Motor

924mm





MST45RE & MST45SE 864mm WIDE MASTER SERIES DUAL TARGET TOP RANGE & DUAL TARGET TOP WITH STORAGE BASE Specification Sheet Issue 003 | Iss