

The ULTRA63522ACS floor model vacuum packaging machine delivers extreme power and the ultimate in technology all incorporated as standard into one unit.

#### **STANDARD FEATURES**

- Stainless steel housing & deep-drawn vacuum chamber for optimal hygiene
- Removable wireless sealing bar
- Insert plates for adjusting vacuum chamber height
- Gas-flush Injecting food-gas for product protection and longer shelf life
- Soft-air Controlled ventilation for protection of product & packaging
- Sensor Control Set percentage pressure for vacuum & gas functions for accurate & constant packaging results
- · Stop button for partial / full cycle interruption
- Digital maintenance program for pump / Operating hours counter / Service indicator programs / Sleeper function etc
- · Service kit for user maintenance

## **ADVANCED CONTROL SYSTEM (ACS) FEATURES**

- Easy to use 4.7 inch full colour LCD screen
- Intuitive programming based on icons + animated process steps
- 20 personalised programs settings can be made on PC
- Settings can be saved ensuring consistent results every time
- Secured access. 3 different access levels with authorisation codes - User / Owner / Dealer
- · Customised screen saver / logo
- Real time / date displayed
- Special programs red meat, marinating, tenderising, sequential and external vacuum
- Liquid control sensor to detect the boiling point of liquid products.
   Developed to pack meat products and liquids such as soups, sauces and marinades. Conserves the quality and weight of product.

## **SERVICE FEATURES**

- Store: Operation hours / process cycles / pump cleaning cycles
- Optional forced service reminder and pump cleaning program
- Service data exportable by USB
- Complete testing mode for all functions
- Software update by USB

## **OPTIONAL ACS FEATURES**

- Zebra Label printer
- Inclined insert plate for packing liquid products
- CUT-OFF Seal Bar

### DIMENSIONS

External dimensions: 695W x 710D x 1025H mm

Chamber: 500W x 520D x 200H mm

Sealing Bar: 2 x 520mm

### **TECHNICAL DATA**

Power supply: 415V 3AC 50Hz (Includes Lead but not Plug)

Power output: 3.5kW Capacity pump: 63 m³/h

Machine cycle: 15-40 seconds


Weight: 143kg

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

# **ULTRA63522ACS**

FLOOR MODEL VACUUM PACKER WITH
GAS FLUSH, SENSOR CONTROL &
ADVANCED CONTROL SYSTEM (ACS)







Busch vacuum pumps, world leaders in vacuum pump technology.



Two years parts and labour warrantly





