

POLAR52-ACS VACUUM PACKAGING MACHINE

The robust, stainless steel POLAR52-ACS vacuum packaging machine is standard equipped with a Busch vacuum pump.

## **STANDARD FEATURES**

- Pump capacity: 63 m3/h Busch vacuum pump
- Standard with 2 seal bars: 2 x 520 mm (left/right)
   Standard double seal (two wires)
- Standard double seal (two wires)
  Silicone holders easily removable for cleaning and maintenance purposes
- Pump maintenance and cleaning program
- Machine cycle: 15-40 sec
- Soft Air to protect the product andvacuum bag
- Sensor control
- Flat work plate
- Advanced control System (ACS) offering 20 personalised programs including:
  - Liquid Control (set and forget)
  - Marinating
  - Tenderising
  - Red Meat
  - Sequential Vacuum - Jar Sealing
- Insert plates included for a faster cycle and product adjustment
- Stainless steel exterior
- IP-65 Rating
- Service kit for standard maintenance included

## **OPTIONAL FEATURES**

- 1-2 Cut-off seal/Bi-active seal
- Cut off seal
- Wide seal (10mm)
- Gas flush (incl. pressed air connection)

External Dimension: 700W x 740D x 1100H mm Chamber (usable space): 520W x 500D x 200H mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

## ACCESSORIES

DIMENSIONS

**TECHNICAL DATA** 

Power (kW): 1.8

Weight: 183kg


RCM Approved:


Voltage (Hz): 3NAC 400V 50Hz


Pump Capacity  $(m^3/h)$ : 63

- Inclined insert plate (for vacuum packing liquids and powders)
- Zebra ZD410 thermal label printer (only in combination with ACS models)











Busch vacuum pumps, world leaders in vacuum pump technology.

Z Two yed

() www.comcater.com.au

Two years parts & labour warranty

contactus@comcater.com.au



MA005A Purevac POLAR52-ACS Specification Sheet Issue 001 | Issue Date: 25/05/2023

 $(\boxtimes)$