

The Australian owned and designed Trueheat RC Series of Gas Cooking Equipment has been developed to meet the operation needs and highest standards demanded by chefs and restaurant owners within a commercial kitchen.

16mm thick steel griddle plate with 16.5MJ/hr burner per 300mm section. Piezo ignition on enclosed oven burners.

25MJ/hr static oven with two oven racks. Interior oven panels manufactured with black vitreous enamel for ease of cleaning.

100% Flame failure controls included as standard.



DIMENSIONS & WEIGHT

External Dimension: 600W x 803D x 1135H mm Net Weight: 161kg Working height : 910mm Oven Interior: 490W x 540D x 320H mm Combustible wall clearance: Side: 150mm, Rear: 150mm

TECHNICAL DATA

Gas Type: Natural or Propane			
Total Output(MJ/hr):	Natural Gas 58	Propane Gas 57	
Burner Ratings (MJ/hr):	Natural Gas	Propane Gas	Ignition Type
Griddle per 300mm:	16.5	16.5	Manual
Oven per 300mm:	25	24	Piezo
Gas Connection: ¾" Female			

AGA approval number: AGA 6652 G

SHIPPING DATA


Shipping Weight: 181kg


Shipping Dimensions: 680W x 900D x 1200H mm


OPTIONAL ACCESSORIES

Part Number:	Description:
GF-CSTRB	Front Castor Swivel with brake to suit RCR models only
GF-CSTR	Rear Castor without brake suits RCR models only
432018-900HK	900mm ¾ flexible gas hose with quick connect fittings and restraint
432018-1200НК	1200mm % flexible gas hose with quick connect fittings and restraint

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.









() www.comcater.com.au

contactus@comcater.com.au