

For more than 25 years, the Vertical Contact Toaster (VCT) has been a staple in foodservice operations, building a reputation for quality, performance, and reliability throughout the world.

The VCT gives buns a consistent, golden brown finish so they don't soak up the juices of the ingredients, helping the sandwich stay firm and delicious. With a dual sided platen, the Vertical Contact Toaster has more capacity than conventional single-sided toasters, allowing operations to quickly serve fresh products to customers without making them wait.

The VCT-25 model features a dial thermostat for adjusting the quality of the toast for a variety of different bread products. The VCT-25 has a preset toast time of 25 seconds. Optional features for the unit include

STANDARD FEATURES

- Dual-sided platen for additional toasting capacity compared to conventional single-sided toasters.
- Dial thermostat to adjust temperature of the platen.
- Space-saving vertical design.
- Continuously moving conveyor for immediate toasting.
- Separate compression adjustments for the heel and crown.



OPTIONAL FEATURES

- Bun Feeder (7001522): Gravity-fed bun feeder
- Butter Wheel (7000703): Stainless Steel butter wheel & pan
- Release sheets (7000250): 10 pack non-stick release sheets

DIMENSIONS

External: 540W x 387D x 591H mm, Weight 35kg
Shipping: 660W x 406D x 838H mm. Weight 40kg

TECHNICAL DATA

Power Supply: 1NAC 240V 1 Phase 50Hz 14.8amp
Output: 3.5kW
Connection: Supplied fitted with 15A Plug and 2m lead

CONTROLLER AS STANDARD

Dial controller

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Bun Specifications

| Model & Mfg. No. | Feeder Opening | Crowns | | Heels | |
|---------------------|----------------|---------|---------|---------|---------|
| | | Min. | Max. | Min. | Max. |
| VCT-20HI 9200583 | (32 mm) | (13 mm) | (22 mm) | (13 mm) | (22 mm) |

