

Tilting bratt pan, Durapan gas open base. 120 litre capacity.

### STANDARD FEATURES

- Anti-splash pouring lip
- Electronic spark ignition
- All controls are serviceable from the front of the unit
- High limit safety device set at 246°C
- Stainless steel clad 16mm cooking surface guaranteed against warping
- Stainless steel coved cornered pans with litre markings
- All stainless steel construction for durability and easy cleaning
- Adjustable, electronic thermostat controls temperature from 37°C to 218°C
- High efficiency heating system with even heat distribution
- Fast heat-up and recovery time—preheats in 11 minutes, full capacity from cold to boiling in 60 minutes
- Spring assist cover with adjustable vent and full width handle
- On/Off switch, thermostat knob and pilots, recessed to avoid breakage
- Four stainless steel, level adjustable feet, rear flanged for bolting
- Two pilot lights; Green = Power on, Amber = Temperature cycling
- Splash proof controls and water tight electrical connections

### ACCESSORIES

- Power Tilt with Hand Tilt Override (PT2)
- Food Strainers for pouring spout (FSSK)
- Vegetable Steamers (VS)
- Poaching Pans (PP)
- Sliding Drain Drawer with Splash Screen (SLD)
- Double or Single (DPK14, SPK14) Pantry Faucet, includes Faucet Mounting Bracket
- Tangent draw-off valve 51mm (TDS2K)
- Folding splash guard for drain draw (SGSLDTR)



### TECHNICAL DATA

External: 915W x 940D x 1067H mm

Clearance: 153mm Rear, 115mm Right Side (for Faucet)

Power Supply: 1NAC 240V, 1 Phase, 0.83 amp  
(1.6m Cable & Plug included) 10A  
Gas Consumption: 80.5mj (NG), 87.5mj (Propane)

Gas Connection: 3/4"

Capacities (per kettle):  
(in 115 gram servings, other sizes may be calculated)  
30 gallons / 120 litres - 960 servings

AGA Approval no.: AGA SC404G






### SHIPPING DATA

Shipping Weight: 228 kg  
Shipping Dimensions: 1117W x 1117D x 1372H mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

### DIMENSIONS

MODEL	A	B	C	G
SGL-30-TR	915mm	812mm	229mm	835mm



NOTE: NON STANDARD ITEMS ARE SHOWN IN GRAY