

The Extra Heavy Duty Master Series' modular approach combines the convenience of custom kitchen design with proven, premium quality components to deliver world class functionality.

Featuring stainless steel construction front and sides, large front 'plate rail' 191mm deep and 2.5mm thick.

Premium 25mm thick griddle with 3 powerful cast iron 'H' burners controlled by Hi-Lo valve for even heat distribution.

Large easy-to-use control knobs sit atop the fully porcelain interior standard oven that accepts full sized sheet pans in both directions with 4-position rack guides. A 42.2MJ 'H' oven burner with flame failure and a strong adjustable door.

STANDARD FEATURES

- 152mm chrome steel adjustable legs
- Piezo Spark ignition for oven
- Modular 1½" front manifold
- Removable front-mounted s/steel grease receptacle
- 250mm stainless steel backguard
- Electric Spark ignition on all pilots

OPTIONAL FEATURES

- Stainless steel oven interior, side(s) or main back
- Fully grooved griddle (or grooved sections)
- Additional oven rack
- Gas regulator ¾" or 1¼"
- Rear gas connection, ¾", 1", or 1¼"
- 4 swivel casters with front brakes
- End caps and cover (NC, Specify)
- Dais base (not for use with "RC" oven)
- Convection oven base, add C to model, eg MST47RC
- Stainless steel common front rail up to 1728mm wide (2 or more units in a battery)
- Gas flex hose & quick disconnect (¾", 1" or 1¼" x 5') w/restraining device



DIMENSIONS

External Dimension: 864W x 962D x 1174H mm

Working height : 924mm

Oven Interior : 667W x 737D x 343H mm

Combustible wall clearance: Side: 356mm, Rear: 152mm

TECHNICAL DATA

Gas Type: Natural or LP

Total Output:	Natural	LP
	137.15MJ	131.85MJ

Burner Ratings:	Natural	LP
Griddle burner	31.65MJ	31.65MJ
Oven	42.2MJ	36.9MJ

Gas Connection: 1½"

Shipping weight: MST47RE 273kg, MST47SE 227kg

AGA approval number

SC383

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

