

Garland's XPress Grill's upper and lower grill plates cook both sides simultaneously, reducing cook times by up to 50%. Upper grill plate is automatically raised and lowered by a lift system powered by a quiet actuator.

Lower griddle plate made of 3/4" (19mm) thick carbon steel, machine ground and highly polished.

Lower grill plate heated by three electric heating elements. Upper platen heated by nickel plated cast aluminum electric heating elements.

Electric top heater provided with replaceable quick release Teflon sheets.

Installation with zero clearance against non-combustible surfaces.



STANDARD FEATURES

- Programmable control for each cooking lane precisely controls:
 - Automatic lifting and lowering of upper platen
 - Cooking gap and time
- EasyTouch™ screen design is simple and intuitive with Press & Go interface
- Advanced temperature control, smart anticipation versus on-off
 - Eliminates temperature overshoot and undershoot
 - Increases temperature uniformity with five independently controlled heat zones -- three on plate and two on platen
 - Each lane can be set to a different temperature for menu flexibility, eg., all-day breakfast
 - Each lane can be turned Off when not required -- saving energy
- USB interface to update menus
- User interface provides advanced diagnostics and error logging for ease of service and increased firsttime fix
- Stainless steel front, top and sides
- Towel bar with bun pan lip
- Stainless steel dual side grease collectors
- Swivel casters (4) with front brakes
- IPX4 water resistant rating
- Two-year limited parts and labour warranty
- Available with 1 upper platen only on either side the left or the right:
 - 1L or -1R
- Grease cans with straight sides for minimum space

OPTIONAL ACS FEATURES

- Grease cans with flared sides to hold optional tool holders
- Optional tool holders
 - 4-inch spatula
 - 6-inch scraper
 - 7-inch wiper

DIMENSIONS

External Dimension: 703W x 876D x 1493H (open) mm

TECHNICAL DATA

Power supply: 415V, 3 Phase, 50Hz (3NAC 415V 50Hz)

Total output: 15.9kW

Breaker Size: 3 x 32A

Supplied: 2.5 metre cable with CLI56PA532 Plug

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

