

Range cooker with gas hob constructed from AISI 304 stainless steel. 2 mm pressed top, designed for flush alignment and to accommodate the water column accessory.

Appliance comprises 4 sealed burners. Safety tap with thermocouple for continuous output control. Main burner ignition by means of permanent, low-energy pilot burner. Pilot burner and thermocouple are located underneath the main burner body, protected from accidental impact and any spills. Hob features radiused corners for ease of cleaning and pan supports in RAAF enamelled cast-iron (acid, alkali and flame resistant).

GN 2/1 conventional electric oven. Oven heated by independently controlled top and bottom heating elements. Thermostat control providing temperature adjustment from 50°C to 300°C. Cooking chamber in stainless steel, dimensions 575x700x300h mm. Oven bottom in cast iron. Oven inner door in stainless steel with labyrinth seal. 4-position selector switch, safety thermostat. Indicator leds indicating correct oven operation. Appliance equipped with height adjustable feet in stainless steel (850-900 mm). IPX5 protection rating.

STANDARD FEATURES

- 2 mm thick pressed stainless tops
- IPX5 water protection
- Modular design
- Interlocking device supplied with all units
- Space at rear for connections
- Flame failure and standing pilot light
- Natural to Propane gas conversion kit
- External gas regulator supplied (specify gas type)

OPTIONAL FEATURES

- Castor kit
- Flexible gas hose with quick disconnect



LEGEND

E = Socket
G = Gas - 1/2"

DIMENSIONS

900D x 800W x 870H mm
Oven: 575D x 700W x 300H mm

TECHNICAL DATA

Gas Type: Natural or Propane
Total Output (Gas): Natural Gas - 102.3MJ/h Propane Gas - 100.3MJ/h
Burners: 3 x 21.6MJ, 1 x 37.5MJ
Gas Connection: 1/2"
Power Supply: 400V 3NAC 50Hz (Lead & Plug not included)
Oven: 6kW
AGA approval number: 7410

SHIPPING DATA

Net Weight: 140kg
Shipping Weight: 154kg
Shipping Dimensions: 1020W x 840L x 1040H mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

