

# Coolstapler®, cooled by circulating air, for crockery baskets 500 mm x 500 mm

#### Make

Manufacturer: **HUPFER®** Model: BDC / 50 - 50No of article: 0161450

# **Dimensions**

Width: 761 mm Depth: 1092 mm Height: 900 mm

#### Execution

### **Structure**

Solid self-supporting structure made from stainless steel.

# **Characteristics**

Basket stacker to store cold foods in portioned cold components in baskets up to 500 mm x 500 mm. Integrated removable stacking platform, 500 x 500 x 150 mm, executed as basket, plastic coated, which can be used as additional space to store crockery. Constant dispensing height by means of manually adjustable tension spring system, lateral guidance of the platform by means of ball bearing with little friction. Hygienically covered by a stainless steel cover hood, double-walled isolation, with profiled handle, cover can be hooked in to the Coolstapler®.

#### Cooling

Cooling by means of the refrigerant agent R 134a, CFC-free. All-around piping for high cooling capacity and uniform food temperatures. Operation by means of ON/OFF-switch with integrated control lamp, visible at great distance. Inherently stable helix cable with angle plug and suspension for the cable.

# **Ergonomics**

Two ergonomically shaped pushing handles with integrated bumpers protecting against injuries at hands and damages at the appliance. Optimum protection against collision due to the two bumpers.

# Chassis

4 swivel castors, 2 of them with brake, castors made from corrosion resistant plastic, free of maintenance, with thread protection, precision ball bearing, 125 mm, according to DIN 18867, part 8.



Fax: +61 7 3399 5311

16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700

Fax: +61 8 6217 0799



#### **Technical Data**

Connected load : 0,22 kW Refrigerating capacity: 0,34 kW

Refrigerating agent: R 134a (CFC-free)
Power supply: 230 V 1N AC 50 Hz

Minimum temp. of crockery: 5 ℃

(closed cover)

Thermal isolation: special insulation
Stacking platform: 500 x 500 x 150 mm
Capacity: 4 baskets, 115 mm
7 baskets, 75 mm high

Upper dispensing height: 750 mm
Enclosure: IPX 4
CE-mark approved

Net weight of the appliance: 75 kg Load capacity: 90 kg