

Coolstapler[®], cooled by circulating air, for crockery baskets 650 mm x 530 mm

Make

Manufacturer : Model: No of article:

HUPFER® BDC / 65 - 53 0161451

Dimensions

Width: Depth: 1212 mm Height:

Execution

Structure

Solid self-supporting structure made from stainless steel.

761 mm

900 mm

Characteristics

Basket stacker to store cold foods in portioned cold components in baskets up to 650 mm x 530 mm. Integrated removable stacking platform, 650 x 530 x 150 mm, executed as basket, plastic coated, which can be used as additional space to store crockery. Constant dispensing height by means of manually adjustable tension spring system, lateral guidance of the platform by means of ball bearing with little friction. Hygienically covered by a stainless steel cover hood, double-walled isolation, with profiled handle, cover can be hooked in to the Coolstapler®.

Cooling

Cooling by means of the refrigerant agent R 134a, CFC-free. All-around piping for high cooling capacity and uniform food temperatures. Operation by means of ON/OFF-switch with integrated control lamp, visible at great distance. Inherently stable helix cable with angle plug and suspension for the cable.

Ergonomics

Two ergonomically shaped pushing handles with integrated bumpers protecting against injuries at hands and damages at the appliance. Optimum protection against collision due to the two bumpers.

Chassis

4 swivel castors, 2 of them with brake, castors made from corrosion resistant plastic, free of maintenance, with thread protection, precision ball bearing, Ø 125 mm, according to DIN 18867, part 8.

from the world of Comcater!

National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695 Fax: +61 3 8699 1299

Melbourne 96-100 Tope Street South Melbourne VIC 3205 Tel: +61 3 8369 4600

Svdnev

20/4 Avenue of the Americas Newington, NSW 2127 Tel: +61 2 9748 3000 Fax: +61 2 9648 4762

Brisbane 1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311

Perth 16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799



www.comcater.com.au



Technical Data

Connected load : Refrigerating capacity:	0,22 kW 0,34 kW
Refrigerating agent: Power supply:	R 134a (CFC-free) 230 V 1N AC 50 Hz
Minimum temp. of crockery: (closed cover)	5 °C
Thermal isolation:	special insulation
Stacking platform:	650 x 530 x 150 mm
Capacity:	4 baskets, 115 mm
	7 baskets, 75 mm high
Upper dispensing height:	750 mm
Enclosure:	IPX 4
CE-mark	approved
Net weight of the appliance:	85 kg
Load capacity:	110 kg

from the world of Comcater!

National Head Office 156 Swann Drive

Melbourne 96-100 Tope Street Derrimut VIC 3030 South Melbourne VIC 3205 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695 Fax: +61 3 8369 4695

Sydney

20/4 Avenue of the Americas Newington, NSW 2127 Tel: +61 2 9748 3000 Fax: +61 2 9648 4762

Brisbane 1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311

Perth 16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799



www.comcater.com.au