

Cup or Bowl dispenser for installation into a worktop, for storing three to eight stacks of round ø 100 - 150 mm round cups, glasses and mugs in a statically heated stacking compartment. The dispenser is made in a robust and hygienic design, from high-quality stainless steel. Designed for installation from above with shelf frame. Features single stacking platform and inner compartment panelling made of anodised-aluminium perforated plate to prevent crockery discolourations. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy to clean stacking compartment from above and via a cleaning opening in the base plate.

Reduced temperature losses and heating time thanks to cover hood made of polycarbonate with 3-point locking mechanism. Heating through stainless steel tubular heating element, infinitely variable using thermostat toggle switch on the equipment, with temperature limiter as per VDE. Current supply via a connecting cable set consisting of two connecting cables with earthed plug and equipment plug and an On/Off switch with integrated indicator light as disconnecter.

The Hupfer in-counter cup or bowl dispenser EBRH-100-150 is used to save space when storing and handing out cups, glasses and mugs without using baskets by means of three to eight self guided stacks on one stacking platform. The use of non-rusting stainless steel springs that are easy to insert and remove provides optimal adjustment options for different loads. The on/off switch can be conveniently integrated into the worktop and requires a cut-out measuring 30 × 22 mm.



DIMENSIONS

448D x 448W x 821H mm Single Stacking compartment

POWER SUPPLY

230V 50 Hz 10A Single Phase (Plugged)

TECHNICAL DATA

Connected Load : 0.6 kW

Temperature Range: 20 - 85 °C

Maximum Temp. of plates: 70 °C

Work Top Cut-Out : ø 445mm - Installation depth 640mm

Thermoelectric supply: Tubular heating element

Capacity: Up to 98 items w/o cover, 104 crockery items with cover

Maximum plate size capacity: ø 100-150 mm crockery

Net Weight of the Appliance: 19.16 kg

Load Capacity: 46 kg

Protection Class: IPX4

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.