

# Basket stacker, heated by circulating air, for baskets 500 mm x 500 mm

### Make

Manufacturer: **HUPFER®** Model: KOUH / 50 - 50 No of article: 0161690

## **Dimensions**

Width: 760 mm Depth: 852 mm Height: 900 mm

## Execution

#### Structure

Solid self-supporting structure made from stainless

#### Characteristics

Basket stacker to receive baskets up to 500 mm x 500 mm, for crockery for soup and hot side dish. Integrated, removable stacking platform made from stainless steel, plastic coated, can be used as additional space for crockery. Constant dispensing height by means of manually adjustable tension spring system, lateral guidance of the platform by ball bearing with little friction. Hygienic closing by means of a plastic cover hood.

# **Heating**

Heating by means of a stainless steel heater with integrated energy module for automatic recirculating air operation, optimum thermal isolation due to a high quality special insulation. Operation by means of ON/OFF-switch with integrated control lamp. Infinitely adjustable and ergonomically shaped temperature control unit at the front side, visible at great distance. Inherently stable helix cable with angle plug, fastener for the plug as cone-shaped dummy socket.

#### **Ergonomics**

Two ergonomically shaped pushing handles with integrated bumpers protecting against injuries at hands and damages at the appliance. Optimum protection against collision due to the two bumpers.

#### Chassis

4 swivel castors, 2 of them with brake, castors made from corrosion resistant plastic, free of maintenance, with thread protection, precision ball bearing, 125 mm, according to DIN 18867, part 8.



Fax: +61 7 3399 5311

Perth 16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799



# **Technical Data**

Stacking platform: basket, plastic coated

500 mm x 500 mm, 6 baskets 115 mm high

Capacity (additional): 9 baskets 75 mm high

Connected load: 2,0 kW

230 V 1N AC 50 Hz Power supply:

Maximum temp. of crockery: 80 ℃

20 ℃ to 110 ℃ Adjustment of thermostat:

IPX 5 Enclosure: Mark of conformity: GS - mark CE-mark approved 72 kg

Net weight of the appliance: Load capacity: 150 kg