

Tilting bratt pan, Durapan gas open base. 150 litre capacity.

STANDARD FEATURES

- · Anti-Splash Pouring Lip
- Electronic Spark Ignition
- · All Controls are serviceable from the front of the unit
- High Limit Safety Device set at 246°C
- Stainless Steel Clad 16mm Cooking Surface Guaranteed against warping
- · Stainless Steel Coved Cornered Pans with Litre Markings
- All Stainless Steel Construction for durability and easy cleaning
- Adjustable, Electronic Thermostat controls temperature from 37°C to 218°C
- · High Efficiency Heating System with even heat distribution
- Fast Heat-Up and Recovery Time-Preheats in 11 minutes, full capacity from cold to boiling in 60 minutes
- · Spring Assist Cover with Adjustable Vent and Full Width Handle
- On/Off Switch, Thermostat Knob and Pilots, recessed to avoid breakage
- Four Stainless Steel, Level adjustable feet, rear flanged for bolting
- Two pilot lights; Green = Power on, Amber = Temperature Cycling
- Splash Proof Controls and Water Tight Electrical Connections

OPTIONAL FEATURES

- Power Tilt with Hand Tilt Override (PT1)
- Food Strainers for pouring spout (FS)
- Vegetable Steamers (VS)
- Poaching Pans (PP)
- · Sliding Drain Drawer with Splash Screen (SLD)
- Double or Single Pantry Faucet (SPK14, DPK14), includes Faucet Mounting Bracket
- · Tangent draw-off valve 51mm (TD2SK)

TECHNICAL DATA

External: 1220W x 940D x 1067H mm

Clearance: 153mm Rear, 115mm Right Side (for Faucet)

Power Supply: 1NAC 240V, 1 Phase, 0.83 amp

(1.6m Cable & Plug included)

Gas Consumption: 115mj (NG), 125mj (Propane)

Gas Connection: 3/4"

Capacities (per kettle):

(in 115 gram servings, other sizes may be calculated)

40 gallons / 150 litres - 1280 servings

AGA Approval no.: AGA SC404G

SHIPPING DATA

Shipping Weight: 283 kg

Shipping Dimensions: 1219W x 1473D x 1372H mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

CODING GUIDE FOR OPTIONS

Power Tilt

OPT10 Sliding Drain Drawer

*add OPT suffix to product code


SGL40TR


GAS TILTING BRATT PANS - 150 LITRE





DIMENSIONS


| MODEL | Α | В | С | G |
|-----------|--------|--------|-------|--------|
| SGL-40-TR | 1220mm | 1118mm | 308mm | 1140mm |














NOTE: NON STANDARD ITEMS ARE SHOWN IN GRAY



National Head Office 156 Swann Drive

Derrimut VIC 3026 +61 3 8369 4600 Tel: Fax: +61 3 8369 4699 96-100 Tope Street South Melbourne VIC 3205 +61 3 8699 1200 +61 3 8699 1299

Melbourne

Sydney

20/4 Avenue of the Americas Newington, NSW 2127

Tel: +61 2 8775 9500 Fax: +61 2 9648 4762

Brisbane

1/62 Borthwick Avenue Murarrie QLD 4172 +61 7 3900 2700 Tel: Fax: +61 7 3399 5311

Perth

Unit 16, 7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799