

Food serving trolley with 1 heatable well

Make

Manufacturer : HUPFER®
Type : SPA/ EB – 1
No of article: 0161470

Dimensions

Width : 678 mm
Depth: 606 mm
Height: 900 mm

Execution

Structure

Food serving trolley made from stainless steel. Seamlessly welded, completely isolated warming well, wet or dry heatable and adjustable; to receive one container GN 1/1 – 200 and its subdivisions. Deep-drawn level indicator. Draining without any residues due to a special inclination of the bottom of the well. Easy recognition of the open respectively shut condition of the drain taps, protected against unintended opening.

Heating

Heating by means of tube frame heating made from stainless steel. Operation by means of ON/OFF switch with integrated control lamp. Infinitely adjustable and ergonomically shaped temperature control unit at the front side, easily visible from a distance. Flexible spiral cable of constant shape with angular socket and additional socket holder. Easy handling due to the well chosen position of the cable at the opposite of the operating side.

Ergonomics

Two ergonomically shaped push handles at the operating side with integrated bumper edges protect against injuries to hands and damages to the device. Castors with disc bumpers at the chassis as protection against collision.

Chassis

Lower frame structure, 25 mm x 25 mm, fully welded, for bottom shelf. 2 swivel castors with total clamps and 2 fixed castors for heavy loads. Castors made from corrosion resistant and maintenance-free plastic with precision ball bearing, Ø 125 mm, according to DIN 18867 part 8.



from the world of Comcater!

National Head Office
156 Swann Drive
Derrimut VIC 3030
Tel: +61 3 8369 4600
Fax: +61 3 8369 4695

Melbourne
96-100 Tope Street
South Melbourne VIC 3205
Tel: +61 3 8369 4600
Fax: +61 3 8699 1299

Sydney
20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 9748 3000
Fax: +61 2 9648 4762

Brisbane
1/62 Borthwick Avenue
Murarrie QLD 4172
Tel: +61 7 3399 3122
Fax: +61 7 3399 5311

Perth
16/7 Abrams Street
Balcatta, WA 6021
Tel: +61 8 6217 0700
Fax: +61 8 6217 0799

COMCATER
- foodservice equipment

www.comcater.com.au

Technical Data

Number of wells:	1
Size of wells:	for GN 1/1 – 200 and Its subdivisions
Capacity:	15 persons
Connected load:	0,7 kW
Electr. connection:	230 V, 1 N AC 50 cyc.
Enclosure:	IPX5
Thermal insulation:	special insulation
Thermostat setting:	30 – 95 °C
Load capacity per castor:	100 kg
Load capacity per trolley:	170 kg
Net weight:	32 kg

from the world of Comcater!

National Head Office

156 Swann Drive
Derrimut VIC 3030
Tel: +61 3 8369 4600
Fax: +61 3 8369 4695

Melbourne

96-100 Tope Street
South Melbourne VIC 3205
Tel: +61 3 8369 4600
Fax: +61 3 8699 1299

Sydney

20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 9748 3000
Fax: +61 2 9648 4762

Brisbane

1/62 Borthwick Avenue
Murarrie QLD 4172
Tel: +61 7 3399 3122
Fax: +61 7 3399 5311

Perth

16/7 Abrams Street
Balcatta, WA 6021
Tel: +61 8 6217 0700
Fax: +61 8 6217 0799



www.comcater.com.au