

## Food serving trolley with 2 heatable wells

678 mm

916 mm

900 mm

### Make

Manufacturer : Type : No of article:

**HUPFER®** SPA/EB-2 0161480

### Dimensions

Width : Depth: Height:

Execution

### Structure

Food serving trolley made from stainless steel. Seamlessly welded, completely isolated warming wells, each separately wet or dry heatable and adjustable; to receive two containers GN 1/1 - 200 and its subdivisions. Deep-drawn level indicator. Draining without any residues due to a special inclination of the bottom of the well. Easy recognition of the open respectively shut condition of the drain taps, protected against unintended opening.

### Heating

Heating by means of tube frame heating made from stainless steel. Classification of the temperature control units by means of stamped numbering. Operation by means of ON/OFF switch with integrated control lamp. Infinitely adjustable and ergonomically shaped temperature control units at the front side, easily visible from a distance. Flexible spiral cable of constant shape with angular socket and additional socket holder. Easy handling due to the well-chosen position of the cable at the opposite of the operating side.

### **Eraonomics**

Two ergonomically shaped push handles at the operating side with integrated bumper edges protect against injuries to hands and damages to the device. Castors with disc bumpers at the chassis as protection against collision.

### Chassis

Lower frame structure, 25 mm x 25 mm, fully welded, for bottom shelf. 2 swivel castors with total clamps and 2 fixed castors for heavy loads. Castors made from corrosion resistant and maintenance-free plastic with precision ball bearing, Ø 125 mm, according to DIN 18867 part 8.

### from the world of Comcater!

National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600

Melbourne 96-100 Tope Street South Melbourne VIC 3205 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695 Fax: +61 3 8699 1299

### Svdnev

20/4 Avenue of the Americas Newington, NSW 2127 Tel: +61 2 9748 3000 Fax: +61 2 9648 4762

Brisbane 1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311

Perth 16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799



www.comcater.com.au



### **Technical Data**

Number of wells: Size of wells:

Capacity: Connected load: Electr. connection: Enclosure: Thermal insulation: Thermostat setting: Load capacity per castor: Load capacity per trolley: Net weight:

2 for GN 1/1 - 200 and its subdivisions for 25 persons 1,4 kW 230 V, 1 N AC 50 cyc. IPX5 special insulation . 30 – 95 ℃ 100 kg 195 kg 44 kg

### from the world of Comcater!

National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695

#### Melbourne 96-100 Tope Street South Melbourne VIC 3205 Tel: +61 3 8369 4600 Fax: +61 3 8699 1299

# Sydney

20/4 Avenue of the Americas Newington, NSW 2127 Tel: +61 2 9748 3000 Fax: +61 2 9648 4762

Brisbane 1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311

Perth 16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799



www.comcater.com.au