

Plate stacker, with 2 stacking tubes heated by circulating air

Make

Manufacturer : Model: No of article:

HUPFER® TEUH-2 / VC 19-26 0161590

Dimensions

Width : Depth: Height:

510 mm 960 mm 900 mm

Execution

Structure

Solid self-supporting structure made from stainless steel.

Characteristics

Plate stacker, heated by circulating air, to receive round plates, Ø 190 to 260 mm. Constant dispensing height by means of manually adjustable tension spring system. Adjustment of the size of the crockery without the necessity of tools, by means of three plastic-coated directions for each tube. Easy cleaning of the stacking pit from the top, each stacking platform additionally equipped with a cleaning aperture in the bottom plate.

Heating

Heating by means of a stainless steel heater with integrated energy module for automatic recirculating air operation, optimum thermal isolation due to a high quality special insulation, additional lining by means of reflecting plates. Operation by means of a ON/OFFswitch with integrated control lamp. Infinitely adjustable and ergonomically shaped temperature control unit at the face side, visible at great distance. Inherently stable helix cable with angle plug, fastener for the plug as cone-shaped dummy socket.

Ergonomics

Two ergonomically shaped pushing handles with integrated bumpers protecting against injuries at hands and damages at the appliance. Optimum protection against collision due to the two bumpers.

Chassis

4 swivel castors, 2 of them with brake, castors made from corrosion resistant plastic, free of maintenance, with thread protection, precision ball bearing, Ø 125 mm, according to DIN 18867, part 8.

from the world of Comcater!

National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695 Fax: +61 3 8699 1299

Melbourne 96-100 Tope Street South Melbourne VIC 3205 Tel: +61 3 8369 4600

Svdnev

20/4 Avenue of the Americas Newington, NSW 2127 Tel: +61 2 9748 3000 Fax: +61 2 9648 4762

Brisbane 1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311

Perth 16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799



www.comcater.com.au



Technical Data

Dimensions of crockery :	Ø 190 to 260 mm
Connected load :	2,0 kW
Maximum crockery temp.:	100 °C
Adjustment of thermostat:	20 °C to 130 °C
Power supply:	230 V 1N AC 50 Hz
Length of the connecting cable:	1800 mm
Quantity of operating condition	
control lamp:	1
-	

Plastic cover, high version:	
Material:	polycarbonate,
	appropriate for dish washers
Stacking height without cover:	645 mm
Stacking height with cover:	735 mm
Capacity without cover:	up to 144 parts
Capacity with cover:	up to 166 parts
Mark of conformity:	GS
CE-mark:	approved
Enclosure:	IPX5

CE-mark.	approve
Enclosure:	IPX5
Net weight of the appliance:	55 kg
Load capacity:	140 kg

from the world of Comcater!

National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695

Melbourne 96-100 Tope Street South Melbourne VIC 3205 Tel: +61 3 8369 4600 Fax: +61 3 8699 1299

Sydney

20/4 Avenue of the Americas Newington, NSW 2127 Tel: +61 2 9748 3000 Fax: +61 2 9648 4762

Brisbane 1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311

Perth 16/7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799



www.comcater.com.au